

OXL4520MK-H2-20-10.000-5

ELECTRICAL SPECIFICATIONS

PARAMETER	SYMBOL	CONDITION	VALUE			UNIT
			Min.	Typ.	Max.	
Nominal Frequency	f_0		10.000			MHz
Supply Voltage	V_s	$V_s \pm 5\%$, at +25°C	4.75	5.0	5.25	V
Power Consumption	P_s	Steady state, at +25°C			0.3	W
	P_w	During warm-up, at +25°C			1.2	W
Initial Frequency Accuracy	$\Delta f/f_0$	At +25°C after 15mins power on ref to nominal frequency with nominal V_c	-100		+100	ppb
Frequency Stability vs. Temp.	$\Delta f/f_0 (T_a)$	$T_a = -20^\circ\text{C} \dots +80^\circ\text{C}$, ref to +25°C	-200		+200	ppb
Aging, After 30 Days of Operation	$\Delta f/\Delta t_d$	Daily	-1		+1	ppb
	$\Delta f/\Delta t_y$	1 st Year	-100		+100	ppb
	$\Delta f/\Delta t_{10y}$	10 years including 1 st year	-300		+300	ppb
Frequency Tuning Range (Slope = Positive)	$\Delta f/f_c (\Delta V_c)$	$V_c = 0$ V ref to center voltage			-0.6	ppm
		$V_c = 2.2$ V center voltage	-0.1		+0.1	ppm
		$V_c = 4.4$ V ref to center voltage	+0.6			ppm
Linearity					10	%
Input Impedance	Z_{in}	At V_c input	25			k Ω
Voltage Reference	V_f		4.3	4.4	4.5	V
Frequency Stability vs. Voltage	$\Delta f/f_0 (\Delta V_{cc})$	$T_a = +25^\circ\text{C}$, $V_s \pm 5\%$	-2		+2	ppb
Frequency Stability vs. Load	$\Delta f/f_0 (\Delta R_L)$	$T_a = +25^\circ\text{C}$, load $\pm 5\%$	-5		+5	ppb
G-Sensitivity		Per axis			1	ppb/g
Warm-up Time		$< \pm 100$ ppb, ref to 1 hour +25°C			1	min
Operating Temperature Range	T_a		-20		+80	°C

OXL4520MK-H2-20-10.000-5**CMOS OUTPUT CHARACTERISTICS**

PARAMETER	SYMBOL	CONDITION	VALUE			UNIT
			Min.	Typ.	Max.	
Output Levels	V _{OL}				+0.4	V
	V _{OH}		+2.4			V
Duty Cycle	DC	Load = 15pF	45	50	55	%
Load				15		pF
Spurious					-70	dBc

PHASE NOISE

PARAMETER	SYMBOL	CONDITION	VALUE			UNIT
			Min.	Typ.	Max.	
@10 Hz Offset	£ (Δ f)			-125	-120	dBc/Hz
@100 Hz Offset	£ (Δ f)			-145	-140	dBc/Hz
@1 kHz Offset	£ (Δ f)			-155	-153	dBc/Hz
@10 kHz Offset	£ (Δ f)			-160	-158	dBc/Hz
@100 kHz Offset	£ (Δ f)			-165	-160	dBc/Hz
@1 MHz Offset	£ (Δ f)			-165	-160	dBc/Hz


ENVIRONMENTAL MECHANICAL CONDITIONS

Storage Temperature range	-55°C to +105°C
Mechanical Shock	MIL-STD-202, Method 213, Test Condition J (30 g, 11 ms half-sine)
Vibration	MIL-STD-202, Method 201, (0.06" Peak to Peak, 10 to 55 Hz)
Humidity	MIL-STD-202, Method 103, Test Condition B (95% at 40°C for 96 hours)


OXL4520MK-H2-20-10.000-5

MECHANICAL DIMENSIONS AND PIN FUNCTIONS


TOP VIEW



SIDE VIEW



SIDE VIEW



PIN	SYMBOL	FUNCTION
1	V	Voltage Control
2	Vf	Reference Voltage
7	GND	Ground
8	OUT	RF Output
14	Vs	Supply Voltage

	Signed	Date
Created	AR	February 27, 2026
Eng. approved	TT	March 4, 2026
REV A	Initial Release	

Raltron Electronics / RAMI Technology USA, LLC, including its affiliates, employees, agents and other persons acting on its behalf (collectively Raltron/RAMI Tech), disclaim any and all liability for any errors or inaccuracies contained in this data sheet. While Raltron/RAMI Tech has made every reasonable effort to ensure the accuracy of all product information, specifications and data contained herein, Raltron/RAMI Tech does not guarantee that the information is accurate, reliable or current. The product information is provided only for reference purposes only and is subject to change, correction or revision, at any time without notice. Raltron/RAMI Tech does not assume any liability arising out of an application or use of any product described herein and disclaims any warranties expressed or implied. The user of products in such applications shall assume all risks of such use and will agree to hold Raltron/RAMI Tech, harmless against all damages.

Copyright © 2026, Raltron Electronics / RAMI Technology USA, LLC. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Raltron Electronics / RAMI Technology USA, LLC.